

PLUMETT / CAPSTAN-WINCH

CAPSTAN-WINCH ON TRAILER

TL2422 DRHZ-1300/8



The trailers provide you extra flexibility to keep you on the road while enjoying all Capstan winch benefits.

Max pulling force: 20 - 40 kN (2000-4000 kg).

The trailer-mounted capstan-winch is designed for laying underground telecommunication and power cables in pre-installed ducts or open trenches as well as for subducting operations.

Its compact design and light weight allows use in tight spaces and its dual capstan system provides pull at constant speed and force.

The cable is automatically paid in and stored by means of a swivelling pulley at a fixed point. This design allows a low-tension winding, regardless of the pulling force and guarantees a stable and constant load on the cable to increase its lifespan.

During the pulling operation, its adjustable limiter automatically stops the winch in case of overload. Its reverse gear allows the cable to be safely and easily unwound.

Our trailers are equipped with a suspension axle and depending on the model with a removable polyester hood or with an overhanging protective canvas.

Available in 10 versions.

Standard version	Capstan-winch		
Type	TL 2422 DRHZ 1300/8	Max. line pull in 1st gear [daN]	2400
Rope dia. [mm]	7-9	Max. line pull in 2nd gear [daN]	500
Max. rope length [m]	1300 (Ø 8 mm)	Speed of pay-in rope in 1st gear [m/min]	0 - 18
Drive unit	Hydraulic	Speed of pay-in rope in 2nd gear [m/min]	0 - 68
Type of engine	Hatz Diesel Supra Silent Pack ID81C	Length, handlebar in high position [mm]	4054
Engine, max. power [kW]	9.6	Width [mm]	1702
Engine, max. RPM [min-1]	3000	Height, wheels in high position [mm]	1547
Hydraulic pressure [bar]	140	Weight of winch without rope [kg]	928



Telephone: +44 (0)1482 620991
 Email: sales@winchsystems.co.uk
 Web: www.winchsystems.co.uk

ADD-ONS



Electronic digital recorder
MP-50



Dynamometer